



ROOFNADO™

AnchorDeck™



SNOW



STORMS



RAIN



HAIL



WIND



UV

NEXGEN™
SYNTHETICS

**ALL TEMP. ALL WEATHER
PERFORMANCE**

AnchorDeck™ is a next generation synthetic roofing underlayment for sloped roof applications.

AnchorDeck™ coating technology allows underlayment to be anchored to the deck prior to applying fasteners. Innovative high-traction walking surface, excellent durability and many other unique performance features make AnchorDeck™ the smart choice for today's roofing professionals.

AnchorDeck™ is designed for use under asphalt shingles, metal in residential applications, synthetic shingles and primed cedar shakes. AnchorDeck™ meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES. AnchorDeck™ not only protects your roof deck, it helps protect Roofers as well.

Ask for it at your nearest roofing distributor today.



- AnchorDeck™ has a unique coating technology which allows underlayment to be anchored to the deck prior to applying fasteners.
- All temp. all weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 212°F)
- 'No stretching around fasteners & no blow-offs!
- Innovative high traction walking surface
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- Meets the performance requirements of CAN/CSA A123.3
- ICC-ES ESR-4055 | FBC Approved – FL21895
- Class A Fire Rating - ASTM E108
- Texas Department of Insurance Approved
- High Definition (HDI) printing
- 90 Days UV Exposure
- 20 year warranty

**PRINT
YOUR LOGO
HERE!**

Attract new customers and increase awareness in your local area!

Visit:
www.roofnado.com/dual-logo
for more information



20 Year
LIMITED WARRANTY